



CONNECTIONS FOR TYPE MR-YG 2POLE 100 AMPERE RELAY.

NOTE:

THE TYPE MR-YG RELAY CONTACTS ARE NORMALLY OPEN WHEN THE COIL IS DE-ENERGIZED AND REQUIRES A 120 VOLT 60 CYCLE UNIT PHOTO CONTROL WHICH HAS CONTACTS CLOSED AT NIGHT FOR ENERGIZING THE TYPE MR-YG RELAY COIL DURING THE STREET LIGHTING ON SCHEDULE.

SINCE STREET LIGHTING LOADS ARE CONTINUOUSLY ENERGIZED FOR LONG PERIODS, THE CONNECTED LOAD SHOULD NOT EXCEED 80% OF THE FUSE RATING.

MAYSTEEL LLC CLAIMS PROPRIETARY RIGHTS IN THE INFORMATION DISCLOSED HEREON. THIS DRAWING IS FURNISHED IN CONFIDENCE ON THE EXPRESS UNDERSTANDING THAT IT OR ANY REPRODUCTION THEREOF WILL BE USED SOLELY FOR THE MANUFACTURE OR PROCUREMENT OF PARTS TO BE FURNISHED TO MAYSTEEL LLC.



TITLE
MR-YG WIRING DIAGRAM & LABEL

A

REV	LTR	DESCRIPTION	DATE	DRAWN	APPROVED	SCALE	DWG NO
				3-3-95	GMM	--	31113600